


**XPoI 1710~2170MHz 90° 18dBi 0°~6° Manual or by optional RCU (Remote Control Unit) Antenna**

**Electrical specifications**


Frequency Range(MHz)	1710-2170		
	1710~1880	1850~1990	1920~2170
Polarization	±45°		
Gain (dBi)	17.7	18	18.2
Horizontal 3dB beamwidth (°)	88	88	90
Vertical 3dB beamwidth (°)	5	4.7	4.3
Front-to-back ratio (dB)	≥23		
Cross-polar ratio (dB)	≥15(±60°≥10)		
Electrical downtilt (°)	0~6		
Sidelobe suppression (dB) (First sidelobe above main beam)	0°...3°...6° 16..15..15		
VSWR	<1.5		
Isolation: intra-system (dB)	≥30		
Intermodulation IM3 (2x43dBm carrier)	≤-150dBc		
Impedance (Ω)	50		
Max. power per input (W) @50°C	300		
RET Model	TY-RCUB20 (External, Not included)		
RET Protocol	AISG 2.0 SRET		
Lightning protection	DC Ground		

**Mechanical specifications**


Connector	2x7/16DIN-Female
Connector position	Bottom
Heightxwidthxdepth (mm)	1980x160x80
Packing size (mm)	2470x210x155
Antenna weight (kg)	11
Installation kit weight (kg)	4.3
Packing weight (kg)	16.6
Wind load (N,at 150km/h) Frontal/Lateral/Rearside	420/124/470
Max. wind velocity (km/h)	216
Radome material	Fiberglass
Radome color	Gray
Mechanical tilt (°)	0~10
Operating temperature (°C)	-50~65
Mounting hardware (mm)	Φ50~Φ115




1710~1880MHz



1850~1990MHz



1920~2170MHz



1710-2170