

**XPoI 790~960MHz 65° 15dBi 0°~15° Manual or by optional RCU (Remote Control Unit) Antenna**

**Electrical specifications**

Frequency Range(MHz)	790~960	
	790~896	870~960
Polarization	±45°	
Gain (dBi)	14.5	15
Horizontal 3dB beamwidth (°)	66	64
Vertical 3dB beamwidth (°)	15	13.5
Front-to-back ratio (dB)	25	
Cross-polar ratio (dB)	≥15(±60°≥10)	
Electrical downtilt (°)	0~15	
Sidelobe suppression (dB) (First sidelobe above main beam)	0°...5°...10°...15° 16...16...15...14	
VSWR	<1.5	
Isolation: intra-system (dB)	≥30	
Intermodulation IM3 (2x43dBm carrier)	≤-150dBc	
Impedance (Ω)	50	
RET Model	TY-ICUB20 (Replaceable, Not included)	
RET Protocol	AISG 2.0 SRET	
Max. power per input (W) @50°C	500	
Lightning protection	DC Ground	

**Mechanical specifications**

Connector	2x7/16DIN-Female
Connector position	Bottom
Heightxwidthxdepth (mm)	1380x270x140
Packing size (mm)	1770x365x220
Antenna weight (kg)	13.7
Installation kit weight (kg)	4.3
Packing weight (kg)	22
Wind load (N,at 150km/h) Frontal/Lateral/Rearside	437/248/439
Max. wind velocity (km/h)	216
Radome material	Fiberglass
Radome color	Gray
Mechanical tilt (°)	0~15
Operating temperature (°C)	-50~65
Mounting hardware (mm)	Φ50~Φ115

